

SolutionPack for Ericsson IMS MTAS

Release number 1.0.0.0

Summary Sheet

June, 2014

- ◆ [Overview](#)..... 2
- ◆ [Technical specifications](#)..... 2
- ◆ [Where to find the latest SolutionPack software](#)..... 3
- ◆ [Collecting performance parameters](#)..... 3
- ◆ [Node, performance category, default file name pattern and 3GPP format](#)..... 4
- ◆ [Configuring the user process limits for a Linux installation](#)..... 5
- ◆ [Installing a SolutionPack](#)..... 5
- ◆ [Confirming report creation](#)..... 6
- ◆ [Troubleshooting](#) 6

Overview

This article explains how to install and configure the SolutionPack for Ericsson IMS Multimedia Telephony Application Server (MTAS). The SolutionPack for Ericsson IMS MTAS monitors the Multimedia Telephony Application Server (MMTel AS), the Scheduled Conference Application Server (Conf AS), and the Service Centralization and Continuity Application Server (SCC AS).

The following describes the servers monitored by this SolutionPack:

- ◆ MMTel AS provides multimedia telephony service and supplementary services according to 3GPP standards and service creation interfaces.
- ◆ Conf AS offers scheduled conference services according to 3GPP standards.
- ◆ SCC AS provides centralized services (ICS) and single radio voice all continuity (SR-VCC) according to 3GPP standards.

This SolutionPack is one of many provided with [Service Assurance Suite](#).

Technical specifications

SolutionPack version

- ◆ 1.0

Compatible Watch4net version

- ◆ 6.3u2 and later

Data collection method

All metrics are parsed through 3GPP standard xml files.

- ◆ XML collector

Performance measurement data

The SolutionPack for Ericsson IMS TSP monitors and collects performance measurement data for this SolutionPack. If you want to generate the reports that show this data, make sure you install the SolutionPack for Ericsson IMS TSP.

Main reports

- ◆ Summary MMTel AS Number of Simultaneous Sessions
- ◆ Summary MMTel AS Simultaneous Sessions in Busy Hour
- ◆ Summary SCC AS Number of Mobile Service Simultaneous Sessions
- ◆ Summary SCC AS Mobile Service Simultaneous Sessions in Busy Hour
- ◆ Summary MTAS Initial Registrations [per second]
- ◆ Summary MTAS Initial De-registration [per second]
- ◆ Summary ASR per CSCF
- ◆ Summary CPS
- ◆ Summary SCC AS (SRVCC) Invocation Attempts [per second]
- ◆ Summary MTAS Number of SIP Requests [per second]
- ◆ Summary MTAS Number of Charging Requests [per second]
- ◆ TSP - MTAS

- MMTel-AS
- SCC-AS
- MRFC
- XDMS (Ut) - Interface
- IMS ADA Authentications (USIM)
- Diameter (Rf - Sh)
- Equipment Related Measurements

Where to find the latest SolutionPack software

SolutionPack software updates

Obtain new or updated SolutionPack software by doing one of the following:

- ◆ Install the latest core software update, such as 6.4. SolutionPacks distributed with core software have a 30-day free evaluation period. If you plan to use the software longer than 30 days, you must install a SolutionPack license before the trial period ends.
- ◆ Upload a `SolutionPackCenter Update.zip` file from **Centralized Management > Packages Management > Packages Listing > Upload**. Since new SolutionPacks distributed in the zip file do not include a 30-day trial license, you must install a license file before installing the SolutionPack.

Collecting performance parameters

Before installing a SolutionPack, you must perform certain steps to ensure the SolutionPack is able to collect performance parameters from various IMS components. These parameters are transferred in 3GPP-compliant XML files from IMS to the Watch4net host using SFTP.

Before you begin

Review the configuration options for the XML collector in the *APG-Text-Parsing-Library.pdf* file located in the `<Install_Dir>/APG/Doc` directory of the Watch4net host.

Procedure

1. Create a directory in the Watch4net host for collecting performance data.

For example: `/opt/IMS/incoming/mtas`

2. On the directory that you just created, change the permissions to `apg`.

For example: `# chown -R apg:apg /opt/IMS/incoming/mtas`

3. Configure the OSS-RC, EMS (Element Management System), mediation node, or other to push the 3GPP-compliant XML files (i.e., Ericsson Report Output Files (ROP)) to the directory created in step 2.

These 3GPP-compliant XML files are listed in the section called *Node, Performance category, Default filename pattern and 3GPP format*.

4. Verify the periodic transfer of the 3GPP-compliant XML files is set accordingly. If your SolutionPack is set to look for updates every five minutes (the default), make sure SFTP is invoked every five minutes as well.
5. SFTP the 3GPP-compliant XML files into the directory that you just created.

Node, performance category, default file name pattern and 3GPP format

You can change the default file name pattern.

The *Ericsson IMS Metrics File* provides a complete listing of the expected counters for each file pattern type. This spreadsheet is available on the EMC support website <http://support.emc.com>.

Table 1 Node, Performance Category, Default file name pattern and 3GPP Format

Node	Performance category	Default file name pattern	3GPP format
MTAS	MtasCDiv	.*_MtasCDiv.*	nPMF 32.401v5.0
MTAS	MtasCharging	.*_MtasCharging.*	nPMF 32.401v5.0
MTAS	MtasComBarring	.*_MtasComBarring.*	nPMF 32.401v5.0
MTAS	MtasConf	.*_MtasConf.*	nPMF 32.401v5.0
MTAS	MtasFcd	.*_MtasFcd.*	nPMF 32.401v5.0
MTAS	MtasFunction	.*_MtasFunction.*	nPMF 32.401v5.0
MTAS	MtasH248	.*_MtasH248.*	nPMF 32.401v5.0
MTAS	MtasHold	.*_MtasHold.*	nPMF 32.401v5.0
MTAS	MtasIdPres	.*_MtasIdPres.*	nPMF 32.401v5.0
MTAS	MtasMmt	.*_MtasMmt.*	nPMF 32.401v5.0
MTAS	MtasMrfc	.*_MtasMrfc.*	nPMF 32.401v5.0
MTAS	MtasXdms	.*_MtasXdms.*	nPMF 32.401v5.0
MTAS	MtasQos	.*_MtasQos.*	nPMF 32.401v5.0
MTAS	MtasScc	.*_MtasScc.*	nPMF 32.401v5.0
MTAS	MtasShInterface	.*_MtasShInterface.*	nPMF 32.401v5.0
MTAS	MtasSip	.*_MtasSip.*	nPMF 32.401v5.0
MTAS	MtasSrvcc	.*_MtasSrvcc.*	nPMF 32.401v5.0
MTAS	MtasSubsData	.*_MtasSubsData.*	nPMF 32.401v5.0
MTAS	MtasTraf	.*_MtasTraf.*	nPMF 32.401v5.0
MTAS	MtasLicenses	.*_MtasLicenses.*	nPMF 32.401v5.0
TSP	IPv4_MeasurementJob	A.*_IPv4.*	nPMF 32.401v5.0
TSP	Diameter	.A.*_Diameter.*	nPMF 32.401v5.0
TSP	PlatformMeasures	.A.*_PlatformMeasures.*	oPMF 32.401v5.0
TSP	IPv6_MeasurementJob	A.*_IPv6.*	oPMF 32.401v5.0
TSP	OamProvision-Measurement	A.*_OamProvisioning.*	nPMF 32.401v5.0

Configuring the user process limits for a Linux installation

Increase the user process limits for the user account to a maximum of 65534. This modification enables services to open 65534 files and 65534 processes when needed.

Before you begin

- ◆ Make sure you have a login with root privileges.
- ◆ The installed on a server running Red Hat Enterprise Linux 6, CentOS Linux 6, or SUSE Linux Enterprise Server (SLES) 11.
- ◆ The name specified for the user account during the installation.

Procedure

1. Open the `/etc/security/limits.conf` file.

2. Add the following lines for the user.

In this example, the user is `apg`.

```
apg    hard    nofile    65534
apg    soft    nofile    65534
apg    hard    nproc     65534
apg    soft    nproc     65534
```

3. Save the file.

4. To restart the services, type the following commands from the `bin` directory of the installation:

```
./manage-modules.sh service stop all
./manage-modules.sh service start all
```

5. To verify the changes, type `su apg -c 'ulimit -n -u'`

Installing a SolutionPack

After you log in as an administrator, you can install a SolutionPack from Centralized Management.

Before you begin

- ◆ Determine whether you need a SolutionPack license file by checking the feature names and expiration dates listed in **Centralized Management > License Management**. If not listed, obtain a license by completing a Support Request (SR) form, which is available on the EMC support website <http://support.emc.com>.
- ◆ Make sure the core modules, such as the Module-Manager, are up-to-date on all servers since not all module dependencies are validated during the SolutionPack installation. See the *Watch4net Installation and Configuration Guide* provides for more information.

Procedure

1. Log in and select **Administration**.
2. Select **Centralized Management** in the Administration tree.
3. Select **SOLUTIONPACK CENTER**.
4. Select the SolutionPack in the **Browse and Install SolutionPacks** screen.
5. Read the summary information and click **Install**.

6. Select the components to install.
 - a. Type the instance name.
 - b. Select the server in one or more list boxes. For example, select the server in the **Data collection** and **Reports** list boxes.
 - c. Click **Next**.
7. For each list box you select, a screen appears.
 - a. Click **Next** after you complete each screen.
 - b. Click **Install** after you complete the last screen.

The installation process begins.

8. Select the maximize arrow next to each component to view the installation process.

When the installation successfully completes, green checkmarks appear.

After you finish

After the installation is complete, select **Centralized Management** › **SolutionPack** to verify the installed SolutionPack.

Confirming report creation

After you install a SolutionPack, you can view its reports.

To view the reports:

Procedure

1. Go to **User Interface** › **Report Library**.
2. Click the SolutionPack to view its reports.

Results

It may take a minimum of three polling cycles to display all relevant information in these reports. By default, one polling cycle is five minutes.

Troubleshooting

Report display problems

- ◆ [What to do if data does not appear in any reports on page 6](#)
- ◆ [What to do if data does not appear in some reports on page 7](#)
- ◆ [Searching for metrics in the database on page 7](#)
- ◆ [Running a scheduled task to import data into reports on page 7](#)
- ◆ [Viewing collector errors in the Collector-Manager log files on page 8](#)
- ◆ [Viewing collector errors from the command line on page 8](#)

What to do if data does not appear in any reports

Procedure

1. After the completion of at least three collection cycles, verify if data is populating into the reports. If there is still no data in the reports, continue to the next step.

2. Run the scheduled task to import data into reports. If there is still no data in the reports, continue to the next step.
3. To view the log files for errors, go to **Centralized Management** and click **Collecting > Collector-Manager::<instance name> > Log Files**.

What to do if data does not appear in some reports

Procedure

1. Run the scheduled task to import data into reports. If there is still no data in the reports, continue to step 2.
2. Search for the metric in the database.
3. To view the log files for errors, go to **Centralized Management** and click **Collecting > Collector-Manager::<instance name> > Log Files**.

Searching for metrics in the database

You can verify that a metric is being collected and used for reporting when you search and find the metric in the database.

Procedure

1. Go to the **Administration** page.
2. Under **Modules**, click **Management of Database Modules**.
3. On the **Metric Selection** page, create the filter, type the number of results, and select the properties to display for the metric.

For example, to list up to 100 results of the SignalWait Time metric with the properties of device and IP, type `name=='SignalWaitTime'` in the **Filter** field, **100** in the **Maximum results** field, and select device and IP for the **Properties to show**.

4. Click **Query**.

A list of the metric results appears. If nothing displays, the metric is not being collected.

Running a scheduled task to import data into reports

After you push a new configuration into a collector, a scheduled task runs and populates the reports with new data. You can manually run the scheduled task to import the data more quickly.

Before you begin

Allow at least three polling cycles to pass before manually running the scheduled task.

Procedure

1. Click **Administration**.
2. Click **Centralized Management**.
3. Expand **Scheduled Tasks**.
4. Click **Database**.
5. Select the **import-properties-Default** task.
6. Click **Run Now**.
7. Confirm success in running the task in the **Last Result** and **Last Result Time** columns.

Viewing collector errors in the Collector-Manager log files

Review the Collector-Manager log files to troubleshoot problems with data collection.

Procedure

1. Click **Administration**.
2. Click **Centralized Management**.
3. Expand **Collecting**.
4. Click the Collector-Manager for your collector instance.

Collector-Manager::*<Collector-Manager instance>* - *<physical_host_ID>*

5. Expand **Log Files** and click the **View File** icon to review the configuration error messages.

Viewing collector errors from the command line

Procedure

- ◆ Use this path to access the log files of the SolutionPack: `/opt/APG/Collecting/Collector-Manager/<ericsson-ims-mtas-instance-name>/logs/collecting-0-0.log`

Copyright © 2014 EMC Corporation. All rights reserved. Published in USA.

Published June, 2014

EMC believes the information in this publication is accurate as of its publication date. The information is subject to change without notice.

The information in this publication is provided as is. EMC Corporation makes no representations or warranties of any kind with respect to the information in this publication, and specifically disclaims implied warranties of merchantability or fitness for a particular purpose. Use, copying, and distribution of any EMC software described in this publication requires an applicable software license.

EMC², EMC, and the EMC logo are registered trademarks or trademarks of EMC Corporation in the United States and other countries. All other trademarks used herein are the property of their respective owners.

For the most up-to-date regulatory document for your product line, go to EMC Online Support (<https://support.emc.com>).